IJIRIS: International Journal of Innovative Research in Information Security
Volume 09, Issue 05, November 2023
E-ISSN: 2349-7017
P-ISSN: 2349-7009
https://www.ijiris.com/archives

News Recommendation Systems: Impediments and Future Prospects

Mahmoud AbouGhaly[1,2]
[1] IT Department, Faculty of Computing and Information, Al-Baha University, Al Baha, KSA.
[2] Mathematics Department, Faculty of Science, AinShams University, Cairo, Egypt.
maboughaly@bu.edu.sa

Publication History
Manuscript Reference No: IJIRIS/RS/Vol.09/Issue05/NVIS10080
Research Article | Open Access | Double-Blind Peer-Reviewed | Article ID: IJIRIS/RS/Vol.09/Issue05/NVIS10080
Received: 20, October 2023|Revised:27, October 2023 | Accepted: 30, October 2023 Published Online: 05, Nov 2023
Volume 2023 | Article ID NVIS10080 http://www.ijiris.com/volumes/Vol09/iss-05/01.NVIS10080.pdf
Article Citation: Mahmoud,AbouGhaly (2023). News Recommendation Systems: Impediments and Future Prospects. International Journal of Innovative Research in Information Security (IJIRIS), Vol.09, Issue 05, 415-424
doi: https://doi.org/10.26562/ijiris.2023.v0905.01 **BibTex key: Mahmoud@2023News**

Copyright: ©2023 This is an open access article distributed under the terms of the Creative Commons Attribution License; which Permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Abstract: News publishers have reduced their usage of traditional newspapers in favour of digital various options such as webpages and specially constructed cell phone applications. In the present world, the internet has recreated information borders and, in addition to smartphone internet access, makes it the most vital medium content for everyone on earth. Users want personalized news recommendations in order to locate relevant news content and avoid information overload. With the growing number of media reports available on social media, tailored news suggestions have become more vital in assisting end users inside discovering relevant and engaging news stories. Traditional recommender systems, on the other hand, frequently fail to account for the constantly changing nature the users' preferences in addition to shifting patterns in news items. To solve this issue, this study offers a context-aware customized data system of recommendations that utilizes contextual information to improve news suggestion individualism. The method entails gathering, extracting, investigating, scrubbing, and arranging a big dataset from 22,657 English publications from 19 individual news outlets online. Four separate recommender frameworks were thought up using different methodologies, including content-based strategies like the TF-IDF Bag-of-Words, and Word2Vec, as well as a related not entirely set in stone by click demeanours. Since it's been thoroughly explored over decades with noteworthy progress in enhancing user interaction, there encore many concerns and obstacles waiting to be researched further.
Keywords: News Recommendations, Personalization, Collaborative Filtering, Click Behavior, Dataset.

I. INTRODUCTION

Today, new media is profoundly embedded in people's lives. As soon as one switches on a computer, all kinds of information and adverts display in windows, and all kinds of comments for various items emerge as soon as one enters an online purchasing platform. Surprisingly, you may realize that the sporting and shopping information that appears is not "irritating," but rather on topics that you take pride in [1]. It seems as in front of the computer screen appears to be an "invisible person" who continues to monitor each user, thinking what sort of news they prefer to read and what goods they likely could purchase. Considering the privacy and timeliness of news resources found on the internet, many customers have switched away from the standard papers to digital news information. Nonetheless, an immense number of information pieces are composed and distributed routinely, making it difficult for purchasers to look through all open news to get the data they are looking [2]. Thus, suited news recommendation code, which attempt to choose content based on users' own interests, are crucial for platforms that publish news to assist users in alleviating an overload of information and improving news reading experience [3]. In recent years, research on tailored news suggestion has received increased interest from industries and universities alike. Figure 1 below. Because of the rising number of headlines obtainable via the internet, readers are finding it growing harder to identify trustworthy and interesting news stories. Traditional suggests systems, on the other hand, frequently struggle to understand the fluid character of consumer interests and shifting patterns in news items. The past suggestion engines recommend items based on the similarities they are to essays in which the user already indicated their interest. In general, the span between two bits of text is used to determine similarity. A small distance suggests a strong sense of resemblance, whereas a large gap indicates a low degree of likeness [4]. People's news tastes, then again, are influenced by different components, including the specific situation and current online entertainment patterns, among others.

It is indispensable to recollect that news frameworks of suggestions go up against extraordinary issues since things change rapidly, peruses' data is confined, and article exactness is incredibly setting subordinate. The suggestion of news items is difficult work due to a very fluid environment, which presents various obstacles, notably continual shifts in the set of articles, a constantly changing set of users, quick changes in user preferences, and so on.



Fig. 1 A customized news recommender system workflow sample

As a result, systems that offer recommendations must be ready of processing continuous inbound media coverage in real time [5]. The intricate prerequisites of news some ideas based on some validity among news items that best meet the user's requirements lead to numerous very interesting study examples when increase the reader's curiosity in it.

1-1- Suggestions Classification of Systems

Due to the sharp rise of social media usage, recommendation systems have emerged as dealing with discipline of study, and many academics began working on endorsement issues based on individual preferences. According to the research, recommendation techniques are commonly classified into three primary approaches alongside a hybrid process, as seen in Figure 2.



Fig. 2. Suggestions Classification of Systems

Recommendation systems mainly can be classified into three broad approaches based on different numbers of technologies classified: (Collaborative Filtering CF approach, Content-based CB approach, and Hybrid-based approach). Content-Based system learns to recommend items that are similar to the ones that the user liked in the past. The similarity of items is calculated based on the features associated with the compared items. For example, if a user has positively rated a movie that belongs to the comedy genre, then the system can learn to recommend other movies from this genre. Collaborative filtering (social filtering) is one of the common widely techniques of the recommender system. It makes recommendations to the active user based on items that other users with similar tastes liked in the past. The similarity in taste of two users is calculated based on the similarity in the rating history of the users. A hybrid recommender system can overcome many problems with collaborative filtering and content-based approaches by combining two methods [6].

These problems have represented as: Sparsity, Cold start, Limited coverage, and Scalability in collaborative filtering. Moreover, limited content and over-specification problems in the content-based method. Knowledge-Based (KB) filtering recommend items based on specific domain knowledge about how certain item features meet users' needs and preferences.

1-2- System of News Recommendations

The media and online communication both play major roles. Twitter and other social media platforms have played a major role in news consumption and promotion. News editors rely on numerous online platforms items to anticipate their audience's interest in news. Diagram 3. Twitter is a rapidly rising social media infrastructure that recently taken on the roles with regard to data intake, creation, and dissemination as news. Twitter messages, known as tweets, are limited to a maximum of 140 characters and can be downloaded and sent from any mobile device.



Fig. 3 media and online communication

By recognizing user-interested subject matter and uncovering undiscovered popular topics, the above technique improves the quality and credibility of news systems that recommend articles [7]. However, it solely evaluates user attention of social media platforms despite taking into account related attention behaviors such as user search histories and search result rates for clicking through. This research offers a context-aware particulars referral system that integrates contextual information to improve recommendation system performance [8]. Click behavior, in particular, is being studied as a kind of contextual information. On the other hand, if something user often clicks on technology-related news stories at various times of a single day or week, then this data may be utilized to tailor news suggestions for that user.

1-3- Modeling by Users

Client displaying is additionally a significant stage in novel news recommender frameworks for deciding clients' specific news inclinations. Understanding shoppers from their ways of behaving is commonly imperative for client displaying calculations. Portrays a model client displaying structure in custom fitted news proposal. As may be obvious, client displaying spins on the demonstrating of information with which clients draw in, and it offers more client viewpoints to get better customized client perception [9]. There are two types of user modeling techniques in present news recommendation methods: feature-based and deep learning-based.

User Modeling Based on Features

Handcrafted features are used to represent users in feature-based user modeling methodologies. Users are designated by their IDs in CF-based approaches, as they are in news modeling [10]. However, data sparsity is a common problem for ID-based user modeling methodologies. As a result, most techniques utilize user behaviors such as announcements clicks to simulate their interest. The majority of feature-based approaches build user profiles using groupings of characteristics retrieved from clicked content [11]. Aside from news content, other strategies make use of additional user attributes to aid in user modeling. For example, audience characteristics (e.g., age, gender, and occupation) are employed in numerous techniques, since people have diverse demographics.

User Modeling Based on Deep Learning

Many news recommendation approaches have used methods of deep learning for modeling consumers in recent years to eliminate the requirement for manual feature engineering. The majority of known algorithms infer user interests based on previous news click behaviour. Several strategies concentrate on gathering historical activated news visualizations. Deep learning-based computational user modeling approaches often seek to gather user visual representations from user behaviors without the need of feature engineering. Many of them derive user interests just from click behavior, because click act is an implicit indicator of a user's affection for news. [12].

1-4- User Modeling Differences in General Suggestion

The client demonstrating approaches utilized with fitted news proposal are like those utilized in everyday suggestion circumstances like web-based retail and film suggestions [13]. Correlation research was likewise led to assess the exactness of different calculations with different gauges drawing near. In this exploration, we give a news suggestion framework that consolidates the information about the client's past commitment with articles (click rehearses) as well as skill about the articles their own to foresee client interest [14]. Our recommended method, which considers both client propensities and article content, expects to give customized ideas that are fit to the client's advantages and convey improved and more appropriate answers for clients [15].

1-5- Objectives

- This research offers a context-aware customized news recommendation engine which utilizes contextual details to improve recommended efficiency.
- A website was built to show the model's potential utility, and we utilized RMSE and MAE to assess the collaborative filtering the model's functionality.

2. RELATED WORKS

(Raza, 2022) Nowadays, an increasing number of news readers consume news online, that they have access to a billion dollars news pieces from a variety of sources. News recommender systems (NRS) are being developed to assist those using identify the proper and relevant material and to alleviate the problem of information overload by revealing news articles that may be of interest to news readers. In this study, we outline the key difficulties confronting the NRS and propose potential solutions based on the most recent findings [16]. (Afsar, 2022) Recommender systems (RSs) are today an inextricably linked aspect of our daily lives. They can help us in locating our favoured goods to purchase, our social network acquaintances, and our favourite movies to watch. The recommendation issue was formerly thought to be an arrangement or prediction issue, and but it is now commonly accepted that expressing it as an ordered decision problem might better demonstrate the power source user-system interaction [17]. (Müller, 2020) The conceptualization of the two fundamental ideas in this discussion, diversity and algorithms, has gotten little exploration in sociological studies in the argument regarding filter bubbles generated by algorithmic news recommendation. This research investigates the impact of numerous recommender systems on various diversity aspects. To that purpose, it maps several values that diversity might serve, as well as a set of criteria that distinguishes a diversified information deliver in this specific idea of unity [18]. (Zhang, 2021) Recommender systems give consumers with individualized service assistance by learning about their prior behaviour and anticipating the present preferences for certain items. AI, particularly computer science and machine learning methodologies and computations, has been automatically employed in the design of recommender systems to increase prediction accuracy and tackle lack of data and cold start problems [19].(Da'u, 2020) Many systems of recommendations (RS) are being used to solve the problem of information overload in domains such as e-commerce as pleasure. and social networking. Although traditional RS approaches have gained amazing success in delivering item suggestions, they still have significant shortcomings, such as starting cold and data sparse [20].

(Kulkarni, 2020) Recommendation systems are becoming increasingly popular in a variety of applications such as e-commerce, movie and music suggestions, tourism, news, advertising, financial markets, social networks, and so on. Traditional recommendation systems model user preferences and make recommendations using either content-based or shared filtering styles [21]. (Jannach, 2021) In circumstances of information overload, recommender applications are apps that help individuals in finding items of interest. Current research frequently adopts a one-shot connection paradigm, in which users' preferences are inferred based on previously observed behavior and the distribution of an ordered set of ideas is the primary, one-way form of user contact [22]. (Zhang, 2019) With the rising wealth of online data, frameworks of proposals have demonstrated to be a brilliant strategy for managing data over-burden. The significance of suggestion systems can't be underlined, taking into account their pervasive use in various applications on the web and their capacity to ease numerous issues related with over-decision [23]. (Deng, 2019) In general, suggestion may be considered as a matching issue, which involves that is, matching appropriate products to appropriate consumers. Nevertheless, due to the large semantic difference between users and stuff, matching users with things in their initial depiction spaces is very tough. Many methodologies have been explored to deal with this issue, and they might be comprehensively ordered into two kinds: illustrative learning-based CF techniques or matched capability learning-based CF draws near [24].

(Ferrari Dacrema, 2019) The preferred strategy for academics interested in the algorithmic elements of systems of recommendations. As a consequence of the increasing curiosity in the field of machine learning in all, it is increasingly tough to keep track of what now reflects the state-of-the-art, for example, for top-n recommendation jobs. At the same time, some recent articles highlight issues in today's applied machine learning research practice, such as repeatability of results or the selection of baselines for presenting new models [25].

3. METHODOLOGY

Our technique begins with data collection, extraction, inquiry, cleaning, and processing. A data pre-processing round is comprised of the gathering of a huge dataset of news stories. Many characteristics, among them title, words, link, author, and keywords, are commonly used to describe data; thus, the feature gathering procedure attempts to locate the appropriate characteristics. The pre-processed data is then sent into the suggested model as input. We created four different news suggestions systems to test their efficacy, employing a variety of modeling methodologies, includes:

- A TF-IDF-based content-based recommender system.
- A recommender system based on content that employs the Bag-of-Words technique.
- A Word2Vec-based content-based recommender system.
- A click-based cooperative filtering recommendation system.

For ways that model media the recommendation as a regression assignment (e.g., indicate information ratings), a few common a regression analysis measurements have been employed to quantify the recommendation achievement, that are as well. Formulated as average absolute error (MAE), the mean squared error (MSE), rooted imply lined an error (RMSE), and a Pearson correlation coefficient (PCC) [26]

$$MAE = \frac{1}{N}\sum_{i=N} | r_i - P_i | (1)$$

$$MAE = \frac{1}{N}\sum_{i=N} (r_i - p_i)^2, (2)$$

$$RMSE = \sqrt{\frac{1}{N}\sum_{i=N} (r_i - p_i)^2}, (3)$$

$$PCC = \frac{1}{N-1}\sum_{i=1}^{N} \left(\frac{r_i - \hat{r}}{\alpha_r}\right)\left(\frac{p_i - \hat{p}}{\alpha_p}\right), (4)$$

The models are assessed using well-known performance metrics such as accuracy and recall. To show the model's applicability, we built a web interface and analysed the method of collaborative filtering using RMSE and MAE [27]. We did a study of contrasts to assess the accuracy of various algorithms with various foundation techniques, such as random and regency. In this part, we will go through all of them in depth. Table 1 shows how many articles obtained prior to cleaning for every news source. Information got from news sites is regularly boisterous and arrives in various structures [28].

News sources	No. of Articles
CNN	2348
BBC	1197
Slate	522
Breitbart	1317
Politico	690
The Hill	1446
CBC	1008
The Washington post	783
The globe and mail	5
Tech Crunch	60
Game Spot	246
Toronto Star	3976
CAN	3621
NPR	945
The New yoked	558
The New Yorktimes	952
WSJ	0
The Week	2341

Table 1 Number of data points obtained for each newspaper prior to cleaning.



Fig. 4 Number of data points obtained for each newspaper prior to cleaning

3.1 The TF IDF Method for Content-Based Recommender Systems

The TF-IDF (Term The regularity and Inverse Documents Frequency) method serves as a widely utilized technique for analysing texts. It gives items in an item's contents weights depending on their use and relevance in the corpus.

$$TF\ (i,j) = \frac{\#\ Times\ word\ i\ appers\ in\ document\ j}{\#\ Words\ in\ document\ j} \quad (5)$$

$$IDF(i,D) = \frac{log_e\ (\#documents\ in\ the\ corpus\ D)}{\#\ Documents\ containing\ Word\ i} \quad (6)$$

$$weight\ (i,j) = TF\ (i,j) \times IDF\ (i,j) \quad (7)$$

3.2 Word2Vec Embedded Content-Based Recommender System

The Substance Based Recommender Frameworks with Word2Vec Implanting is a generally involved strategy in the domain of regular language handling (NLP) to take care of assessing and ordering semantic shared traits of words in enormous examples of language information in view of their distributional properties [29]. We used connection scores to find the articles that were the nearest to the articles the client was zeroing in on for the reason to propose distributions to them in view of their snap conduct. The practically identical articles were then organized in a diminishing number of association assessments, with the most comparative at the most significant level and the most different at the base. Emma Brocken, [30].

4. RESULTS

We used two criteria to evaluate the models: accuracy and recall. Precision measures the fraction of relevant items recommended to the user, whereas recall measures the amount of relevant articles advised to the user. A web interface was built to show the model's applicability, and the system for collaborative filtering was analysed using RMSE and MAE.

	Article_id	Title	Correlation
0	Content_130	Forever chemiclas find fast food wrappers	1.000000
1	Content_4005	Brown rice natti vogel examine gay man stuggle selfimage	0.136920
2	Content_5980	Red dot 20121222 ste 36 amaze celestial race	0.165936
3	Content_2633	Epa defend sott pruitts multiple email address stander practice since cilnton	0.116599
4	Content_2452	dolester miless lemon meringue tart reciepe	0.109983

Fig. 5 Preferred articles based on user click stream behavior

Table 2 Using click behavior to evaluate the results of a collaborative-based recommender system

	Fold 1	Fold 2	Fold 3	Fold 4	Fold 5	Mean	Std
MAE	0.2659	0.6926	0.8975	0.9462	0.1699	0.2569	0.1549
MSE	0.2659	0.2599	0.2497	0.2164	0.1648	0.2569	0.5691
RMSE	0.299	0.1469	0.264	0.2498	0.2564	0.1248	0.2649
Fit time	10.66	1.56	99.9	5.69	8.59	9.26	0.49
Test time	0.69	0.25	0.69	0.22	0.99	0.82	0.36



Fig. 6 Using click behavior to evaluate the results of a collaborative-based recommender system

The calculation has additionally been improved to recommend content in light of their topic and classes. The discoveries in Figure 4 show that the model works really hard of proposing articles that can be connected semantically to the request title and are in a similar classification comparing to the question thing.

4.1 Comparison Investigation and User Response

To investigate the viability of the proposed news suggestion calculations, we utilized a mix of normal examination measures and client contribution to survey their viability. We had the option to dispassionately investigate idea execution and assess continuous client experience thanks to the actions we utilized. Such baselines permit us to look at the adequacy of the proposed models to less difficult methods, and they might be utilized as a marker for future concentration in this space. Table 3 displays the accuracy and Recall ratings for all recommender systems.

Table 3 Feedback from users on the suggested news recommendation algorithm

Feedback category	Number of issues
Positive	42
Negative	6
Neutral	7



Fig. 7 Feedback from users on the suggested news recommendation algorithm

As per the outcomes, 42 clients offered positive input, 6 provided antagonistic criticism, and 7 offered aloof analysis. The enormous number of positive responses shows that the calculation utilized was effective in recommending significant reports to peruse [31]. The negative reaction distinguishes regions for development; while the unbiased criticism demonstrates that a few clients preferred the offered material dull, implying that the proposal system might be upgraded further. These discoveries show that the calculation functioned admirably generally, despite the fact that there is opportunity to get better. Negative comments about the nature of the article may be credited to the data's sources used to create ideas. Moreover, utilizing real client click information rather than reproduced information might help tackle fitting worries. Improvements to the system's architecture and layout of the interface can help in the resolution of technical challenges and the enhancement of the user experience [32]. All in all, these discoveries give significant bits of knowledge into the proposed news suggestion calculation's assets and disadvantages, as well as future exploration regions to increment news proposal adequacy.

5. DISCUSSION

Each of the four types has advantages and disadvantages. Although systems based on content can recommend content based on similarities in their content, they do not consider additional criteria such as user tastes or past browsing behavior. The cooperative sifting approach in light of snap ways of behaving can propose articles in view of equivalent clients' preferences and past perusing propensities, yet it is obliged by the entrance and type inside the client thing network. The BoW model is a direct and proficient technique to content-based suggestion frameworks. It does, in any case, have specific limitations. The BoW model, for instance, doesn't consider the succession of the expressions or the circumstance wherein they appear in the text. The substance-based recommender framework worked around Word to Vector (W implant might be more viable than different models in gathering the phonetic meaning of the message. By incorporating sorts and makers, the model may likewise give additional background information and increment the suggestion framework's exactness [33]. The collaborative filters model based on click activity is the only one that takes user behavior into account, and it has a low RMSE as well as with an average MAE of 0.0252 and a means the RMSE = 0.0364. The system is capable of forecasting the evaluations of the test results properly and in a fair length of time. Another drawback is that our strategy doesn't think about the assortment of reports the peruses could be keen on. Future review could take a gander at the utilization of variety mindful suggestion methods that consider the variety of suggested things straightforwardly.

6. FUTURE DIRECTIONS

By completely assessing existing news proposal calculations in numerous viewpoints, we can see that customized news suggestions approaches have made huge improvement as of late. However, numerous hurdles and unsolved issues persist. As a result, in this part, we discuss various potential future avenues worth investigating.

Deep News Understanding- At the core of custom-made news proposal is news demonstrating. It very well may be upgraded in the accompanying ways. In the first place, message getting a handle on is an essential trouble in news displaying, while at the same time introducing approaches might be unequipped for appropriately fathoming news composed content.

Universal Customer Modeling- Analysing people' interest in news requires the usage of user modeling. Be that as it may, it is trying to actually and completely address the dynamic and different client interest for media suggestion.

Customized evaluating that is Effective and Efficient- News assessing is a significant stage in making custom-made news ideas. To increment news positioning, there are three key examination headings.

Recommendation for Hyperbolic Image Learning for Journalism : Most contemporary news recommendation systems learn news and user representations in Euclidean space.

Challenges in the News Recommend Domain: Building a system of recommendations for news suggestions appears simple at first glance, but it is not. Finding the appropriate news article to recommend is a tactical effort based on news similarities between news articles or user tastes and interests [34].

The item cold-start issue- is one of the most serious issues in all collaborative filtering-based recommendation systems.

Clear Users Feedback- Without clear news comments from readers, it is difficult to monitor or comprehend reader satisfaction with the article, whether the article was liked or not.

Periodic Variations in User Interests- Predicting a user's future interest is a significant difficulty and extremely dynamic in the news domain in all forms of user-based recommendations.

Changing Customer Interest Due to subject Diverging- One of the key issues in adaptive news suggestion is subject divergence, which occurs when the gist of the first news for the users that follow additional news readers changes throughout conversation.

User Modeling or Profiling- In order to provide personalized personal recommendations of news articles, a full user profile that includes user preferences and interests must be maintained. Any collaboration recommender system must include user profiling.

News Recommendation from numerous Sources- News readers like to read news items from numerous sources to gain an in-depth comprehension of a recent occurrence, the most recent development in a news topic, or diverse viewpoints and points of view.

7. CONCLUSION

This research provided a context-aware customized news recommendation engine that utilizes contextual information to improve news suggestion personalization. We utilized an immense dataset of 22,657 reports from 19 prestigious internet-based news sources to build four distinct suggestion frameworks in view of content-based approaches (TF-IDF, Bag-of-Words, and Word2Vec) and shared sifting in light of clicking conduct. We give a top to bottom examination of the customized news exhortation field in this overview, including the advances that are available in various centre modules of a tweaked news recommender, the informational collection and measurements for evaluating execution, the central issues in regard to making customized news suggestion frameworks, and the conceivable future ways to be investigated. By focusing on the significance of logical information and collaboration in tweaking news ideas, the review adds to the assortment of writing on news proposal frameworks.

8. FUTURE WORKS

It also serves as a guide for future inquiry and exploration of many dimensions. Here are some tips for developing an accurate news advocate system.

- To develop a collection of baseline dataset that spans various scenarios using various recommendation methodologies, as well as to establish its assessment parameters.
- News suggestions from numerous sources, either through a news site like News from Google, any other option for hybrid or content-based strategies to lessen reliance on third parties through carefully analysed news item qualities.

REFERENCES

1. Daniel Billsus and Michael J Pazzani. 2000. User modeling for adaptive news access. User Modeling and User-adapted Interaction 10, 2-3 (2000), 147-180. https://doi.org/10.1023/A:1026501525781
2. Toine Bogers and Antal Van den Bosch. 2007. Comparing and evaluating information retrieval algorithms for news recommendation. In Recsys. 141-144. https://doi.org/10.1145/1297231.1297256

3. Darvishy, A., Ibrahim, H., Sidi, F., Mustapha, A.: HYPNER: a hybrid approach for personalized news recommendation. IEEE Access 8, 46877-46894 (2020). https://doi.org/10.1109/ACCESS.2020.2978505
4. Wang, H., Zhang, F., Xie, X., Guo, M.: DKN: Deep knowledge aware network for news recommendation. In: Proceedings of the 2018 world wide web conference, Lyon, France, pp. 1835-1844, 2018. https://doi.org/10.1145/3178876.3186175
5. Qi, T., Wu, F., Wu, C., Yang, P., Yu, Y. et al.: HieRec: Hierarchical user interest modeling for personalized news recommendation. arXiv preprint arXiv:2106.04408, 2021. https://doi.org/10.18653/v1/2021.acl-long.423
6. Panteli, M., Piscopo, A., Harland, A., Tutcher, J., Moss, and FM.: Recommendation systems for news articles at the BBC. In: Proceedings of the 7th International Workshop on News Recommendation and Analytics in conjunction with 13th ACM Conference on Recommender Systems, INRA@RecSys, Copenhagen, Denmark, pp. 44-52. 2019.
7. Ines Chami, Zhitao Ying, Christopher Ré, and Jure Leskovec. 2019. Hyperbolic graph convolutional neural networks. NeurIPS 32 (2019), 4868-4879.
8. Cheng Chen, Xiangwu Meng, Zhenghua Xu, and Thomas Lukasiewicz. 2017. Location-aware personalized news recommendation with deep semantic analysis. IEEE Access 5 (2017), 1624-1638. https://doi.org/10.1109/ACCESS.2017.2655150
9. Wei Chen, Li-jun Zhang, Chun Chen, and Jia-jun Bu. 2009. A hybrid phonic web news recommender system for pervasive access. In Proc. of the WRI Int. Conf. on Commun. And Mobile Compute. Vol. 3. IEEE, 122-126. https://doi.org/10.1109/CMC.2009.20
10. Sungmin Cho, Hongjun Lim, Keunchan Park, Sungjoo Yoo, and Eunhyeok Park. 2021. on the Overlooked Significance of Underutilized Contextual Features in Recent News Recommendation Models.
11. Antoine Bordes, Nicolas Usunier, Alberto Garcia-Duran, Jason Weston, and Oksana Yakhnenko. 2013. Translating embeddings for modeling multi-relational data. In NIPS. 1-9.
12. Hugo L Borges and Ana C Lorena. 2010. A survey on recommender systems for news data. In Smart Information and Knowledge Management. Springer, 129-151. https://doi.org/10.1007/978-3-642-04584-4_6
13. Michel Capelle, Flavius Frasincar, Marnix Moerland, and Frederik Hogenboom. 2012. Semantics-based news recommendation. In WIMS. 1-9. https://doi.org/10.1145/2254129.2254163
14. Michel Capelle, Frederik Hogenboom, Alexander Hogenboom, and Flavius Frasincar. 2013. Semantic news recommendation using wordnet and bing similarities. In SAC. 296-302. https://doi.org/10.1145/2480362.2480426
15. Michel Capelle, Marnix Moerland, Frederik Hogenboom, Flavius Frasincar, and Damir Vandic. 2015. Bing-SF-IDF+ a hybrid semantics-driven news recommender. In SAC. 732-739. https://doi.org/10.1145/2695664.2695700
16. Raza, S., & Ding, C. (2022). News recommender system: a review of recent progress, challenges, and opportunities. Artificial Intelligence Review, 1-52. https://doi.org/10.1007/s10462-021-10043-x
17. Afsar, M. M., Crump, T., & Far, B. (2022). Reinforcement learning based recommender systems: A survey. ACM Computing Surveys, 55(7), 1-38. https://doi.org/10.1145/3543846
18. Müller, J., Trilling, D., Helberger, N., & van Es, B. (2020). Do not blame it on the algorithm: an empirical assessment of multiple recommender systems and their impact on content diversity. In Digital Media, Political Polarization and Challenges to Democracy (pp. 45-63). Routledge. https://doi.org/10.4324/9780429243912-4
19. Zhang, Q., Lu, J., & Jin, Y. (2021). Artificial intelligence in recommender systems. Complex & Intelligent Systems, 7, 439-457. https://doi.org/10.1007/s40747-020-00212-w
20. Da'u, A., & Salim, N. (2020). Recommendation system based on deep learning methods: a systematic review and new directions. Artificial Intelligence Review, 53(4), 2709-2748. https://doi.org/10.1007/s10462-019-09744-1
21. Kulkarni, S., & Rodd, S. F. (2020). Context Aware Recommendation Systems: A review of the state of the art techniques. Computer Science Review, 37, 100255. https://doi.org/10.1016/j.cosrev.2020.100255
22. Jannach, D., Manzoor, A., Cai, W., & Chen, L. (2021). A survey on conversational recommender systems. ACM Computing Surveys (CSUR), 54(5), 1-36. https://doi.org/10.1145/3453154
23. Zhang, S., Yao, L., Sun, A., & Tay, Y. (2019). Deep learning based recommender system: A survey and new perspectives. ACM computing surveys (CSUR), 52(1), 1-38. https://doi.org/10.1145/3158369
24. Deng, Z. H., Huang, L., Wang, C. D., Lai, J. H., & Philip, S. Y. (2019, July). Deepcf: A unified framework of representation learning and matching function learning in recommender system. In Proceedings of the AAAI conference on artificial intelligence (Vol. 33, No. 01, pp. 61-68). https://doi.org/10.1609/aaai.v33i01.330161
25. Ferrari Dacrema, M., Cremonesi, P., & Jannach, D. (2019, September). Are we really making much progress? A worrying analysis of recent neural recommendation approaches. In Proceedings of the 13th ACM conference on recommender systems (pp. 101-109). https://doi.org/10.1145/3298689.3347058
26. Pazzani, M.J., Billsus, D.: Content-based recommendation systems. In: Brusilovsky, P., Kobsa, A., Nejdl, W. (eds.) the adaptive web: methods and strategies of web personalization. Lecture Notes in Computer Science, Springer (2007).

27. Epure, E. V., Kille, J. E. Ingvaldsen, R. Deneckere, C. Salinesi et al.: Recommending personalized news in short user sessions. In Proceedings of the Eleventh ACM Conference on Recommender Systems, Como, Italy, pp. 121-129, 2017. https://doi.org/10.1145/3109859.3109894
28. Li,L.,Zheng, L., Yang, F., Li, T.: Modeling and broadening temporal user interest in personalized news recommendation. Expert Syst. Appl. 41(7), 3168-3177 (2014). https://doi.org/10.1016/j.eswa.2013.11.020
29. Resnick, P., Iacovou, N., Suchak, M., Bergstrom, P., Riedl, J.: GroupLens: an open architecture for collaborative filtering of Netnews. In: Proceedings of the ACM Conference on Computer Supported Cooperative Work, New York, NY, USA, pp. 175-186, 1994. https://doi.org/10.1145/192844.192905
30. Emma Brocken, Aron Hartveld, Emma de Koning, Thomas van Noort, Frederik Hogenboom, Flavius Frasincar, and Tarmo Robal. 2019. Bing-CF-IDF+: A Semantics-Driven News Recommender System. In CAiSE. Springer, 32-47. https://doi.org/10.1007/978-3-030-21290-2_3
31. Robin Burke. 2017. Multisided fairness for recommendation. arXiv preprint arXiv:1707.00093 (2017).
32. Sirian Caldarelli, Davide Feltoni Gurini, Alessandro Micarelli, and Giuseppe Sansonetti. 2016. A Signal-Based Approach to News Recommendation... In UMAP (Extended Proceedings).
33. Iván Cantador and Pablo Castells. 2009. Semantic contextualisation in a news recommender system. (2009).
34. Iván Cantador, Pablo Castells, and Alejandro Bellogín. 2011. An enhanced semantic layer for hybrid recommender systems: Application to news recommendation. Int. Journal on Semantic Web and Inf. Syst. 7, 1 (2011), 44-78. https://doi.org/10.4018/jswis.2011010103

IJIRIS © 2014-23, AM Publications -All Rights Reserved